


## **Uniqe characteristics**





# FM Mattsson tronic WMS, hospital mixer, battery operation

Article number: 16612500 Description: Chrome

- WMS-mixers with possibilities of wireless connection (subscription is required)
- Adjustable hygiene flushing, intervals and rinsing time (to avoid stagnant water)
- Logging of all flushings with point of time, water consumption and temperature for individual mixer or group of mixers (minimum, maximum and average values)
- · Battery monitoring
- Built-in temperature measurements of mixed water temperature
- Programmable temperature stop, the mixer will turn off directly at set maximum temperature
- · With thermostatic function
- Temperature handle with safety stop at 38°C
- Adjustable maximum temperature, pre-set to 42°C
- · Soft closing solenoid valve
- · Safe against vandalism, complete in metal
- Eco (energy and water saving constant flow aerator, 5 l/min at 200– 600 kPa)
- · With self-draining spout
- The mixer is activated by holding a hand in front of the sensor eye.
  Once started the mixer will run for 10 seconds, but can be turned off manually by holding a hand in front of the sensor again
- Flush Timeout safety shut-off to prevent flooding, maximum of 30 seconds
- 30 sec. rinse time via sensor
- · Can be turned off by solenoid valve (eg for cleaning)
- Low power consumption Long life
- · Equipped with system for thermal disinfection against legionella
- Battery operation, can be converted to mains operation
- IP class sensor, IP67

# **FM Mattsson**

• Approved non-return valves, EN-Standard EN1717

#### Installation:

- Note! Gateway and a subscription is required for WMS
- · Automatic sensor calibration
- Easy to change battery, without turning off the water supply
- Mains operation requires installation of the AC adapter FMM S600132, and power supply FMM S600129 alternatively transformer FMM S600128

## Settings:

- Adjustable max temperature
- With Gateway and WMS:
  - Hygiene flushing with adjustable time and intervals
  - Initiate hot water rinsing
  - Programming of rinsing times, temperature alarm och temperature stops
  - Alert signal if exceeding the time limit for stagnant water (the latest flushing)